



TGFU.R39020 Roofing Systems

[Page Bottom](#)

Roofing Systems

[See General Information for Roofing Systems](#)

CURACRETO S A DE C V

R39020

AV 1 DE MAYO # 8A

COLONIA TACUBAYA

11870 CIUDAD DE MEXICO, MEXICO MEXICO

MODIFIED BITUMEN MEMBRANE SYSTEMS

Class A

1. Deck: NC

Incline: 1/4

Base Sheet: — One or more plies Technoply SBS SV 140 L, Technoply SBS SV 220 L, Technoply SBS SV 300 L, Technoply SBS SP 250 L, Technoply SBS SP 300 L, Technoply SBS SP 400 L, Testarosso SBS 250 L, Testarosso SBS 300 L, Technoply SBS BFG 140 S, Technoply SBS BFG 220 S, Technoply SBS BFG 300 S, Technoply SBS BP 250 S, Technoply SBS BP 300 S, Technoply SBS BP 400 S, Testarosso SBS 250 S, or Testarosso SBS 300 S, mechanically fastened or torched.

Membrane: — Technoply SBS SV 300 Aluminum Flake, Technoply SBS CFG 300 Aluminum Flake, Technoply SBS SV 350 Aluminum Flake, Technoply SBS CFG 350 Aluminum Flake, Technoply SBS SV 400 Aluminum Flake, Technoply SBS CFG 400 Aluminum Flake, Technoply SBS SP 300 Aluminum Flake, Technoply SBS SP 300 Aluminum Flake, Technoply SBS SP 350 Aluminum Flake, Technoply SBS SP 350 Aluminum Flake, Technoply SBS SP 400 Aluminum Flake, Technoply SBS SP 400 Aluminum Flake, torched.

2. Deck: C-15/32

Incline: 1/4

Insulation (optional): — Polyisocyanurate , perlite, glass fiber, wood fiber, mineral fibreboard, any combination, any thickness, loose laid or mechanically fastened.

Barrier Board: — One or more layers Georgia-Pacific Gypsum LLC "DensDeck® Roofboard" or "DensDeck® Prime Roofboard" or "DensDeck® DuraGuard™ Roofboard", minimum 1/4-in. thick, or United States Gypsum Co. "SECUROCK® Roof Board" (Type FRX-G) or "SECUROCK® Glass-Mat Roof Board" (Type SGMRX), minimum 1/4-in. thick.

Base Sheet: — One or more plies Technoply SBS SV 140 L, Technoply SBS SV 220 L, Technoply SBS SV 300 L, Technoply SBS SP 250 L, Technoply SBS SP 300 L, Technoply SBS SP 400 L, Testarosso SBS 250 L, Testarosso SBS 300 L, Technoply SBS BFG 140 S, Technoply SBS BFG 220 S, Technoply SBS BFG 300 S, Technoply SBS BP 250 S, Technoply SBS BP 300 S, Technoply SBS BP 400 S, Testarosso SBS 250 S, or Testarosso SBS 300 S, mechanically fastened or torched.

Membrane: — Technoply SBS SV 300 Aluminum Flake, Technoply SBS CFG 300 Aluminum Flake, Technoply SBS SV 350 Aluminum Flake, Technoply SBS CFG 350 Aluminum Flake, Technoply SBS SV 400 Aluminum Flake, Technoply SBS CFG 400 Aluminum Flake, Technoply SBS SP 300 Aluminum Flake, Technoply SBS SP 300 Aluminum Flake, Technoply SBS SP 350 Aluminum Flake, Technoply SBS SP 350 Aluminum Flake, Technoply SBS SP 400 Aluminum Flake, Technoply SBS SP 400 Aluminum Flake, torched.

3. Deck: NC

Incline: 1/4

Base Sheet: — One or more plies Technoply SBS SV 140 L, Technoply SBS SV 220 L, Technoply SBS SV 300 L, Technoply SBS SP 250 L, Technoply SBS SP 300 L, Technoply SBS SP 400 L, Testarosso SBS 250 L, Testarosso SBS 300 L, Technoply SBS BFG 140 S, Technoply SBS BFG 220 S, Technoply SBS BFG 300 S, Technoply SBS BP 250 S, Technoply SBS BP 300 S, Technoply SBS BP 400 S, Testarosso SBS 250 S, or Testarosso SBS 300 S, mechanically fastened or torched.

Membrane: — Technoply SBS FR SV 300 G, Technoply SBS FR CFG 300 G, Technoply SBS FR SV 350 G, Technoply SBS FR CFG 350 G, Technoply SBS FR SV 400 G, Technoply SBS FR CFG 400 G, Technoply SBS FR SP 300 G, Technoply SBS FR SP 300 G, Technoply SBS FR SP 350 G, Technoply SBS FR SP 350 G, Technoply SBS FR SP 400 G, Technoply SBS FR SP 400 G, torched.

4. Deck: C-15/32

Incline: 1/4

Insulation (optional): — Polyisocyanurate , perlite, glass fiber, wood fiber, mineral fibreboard, any combination, any thickness, loose laid or mechanically fastened.

Barrier Board: — One or more layers Georgia-Pacific Gypsum LLC "DensDeck® Roofboard" or "DensDeck® Prime Roofboard" or "DensDeck® DuraGuard™ Roofboard", minimum 1/4-in. thick, or United States Gypsum Co. "SECUROCK® Roof Board" (Type FRX-G) or "SECUROCK® Glass-Mat Roof Board" (Type SGMRX), minimum 1/4-in. thick.

Membrane: — Technoply SBS FR SV 300 G, Technoply SBS FR CFG 300 G, Technoply SBS FR SV 350 G, Technoply SBS FR CFG 350 G, Technoply SBS FR SV 400 G, Technoply SBS FR CFG 400 G, Technoply SBS FR SP 300 G, Technoply SBS FR SP 300 G, Technoply SBS FR SP 350 G, Technoply SBS FR SP 350 G, Technoply SBS FR SP 400 G, Technoply SBS FR SP 400 G, torched.

5. Deck: NC

Incline: 1/2

Base Sheet: — One or more plies Technoply SBS SV 140 L, Technoply SBS SV 220 L, Technoply SBS SV 300 L, Technoply SBS SP 250 L, Technoply SBS SP 300 L, Technoply SBS SP 400 L, Testarosso SBS 250 L, Testarosso SBS 300 L, Technoply SBS BFG 140 S, Technoply

SBS BFG 220 S, Technoply SBS BFG 300 S, Technoply SBS BP 250 S, Technoply SBS BP 300 S, Technoply SBS BP 400 S, Testarosso SBS 250 S, or Testarosso SBS 300 S, mechanically fastened or torched.

Membrane: — Technoply SBS FR SV 300 Aluminum Flake, Technoply SBS FR CFG 300 Aluminum Flake, Technoply SBS FR SV 350 Aluminum Flake, Technoply SBS FR CFG 350 Aluminum Flake, Technoply SBS FR SV 400 Aluminum Flake, Technoply SBS FR CFG 400 Aluminum Flake, Technoply SBS FR SP 300 Aluminum Flake, Technoply SBS FR SP 300 Aluminum Flake, Technoply SBS FR SP 350 Aluminum Flake, Technoply SBS FR SP 350 Aluminum Flake, Technoply SBS FR SP 400 Aluminum Flake, Technoply SBS FR SP 400 Aluminum Flake, torched.

6. **Deck:** C-15/32

Incline: 1/2

Insulation (optional): — Polyisocyanurate , perlite, glass fiber, wood fiber, mineral fibreboard, any combination, any thickness, loose laid or mechanically fastened.

Barrier Board: — One or more layers Georgia-Pacific Gypsum LLC "DensDeck® Roofboard" or "DensDeck® Prime Roofboard" or "DensDeck® DuraGuard™ Roofboard", minimum 1/4-in. thick, or United States Gypsum Co. "SECUROCK® Roof Board" (Type FRX-G) or "SECUROCK® Glass-Mat Roof Board" (Type SGMRX), minimum 1/4-in. thick.

Base Sheet: — One or more plies Technoply SBS SV 140 L, Technoply SBS SV 220 L, Technoply SBS SV 300 L, Technoply SBS SP 250 L, Technoply SBS SP 300 L, Technoply SBS SP 400 L, Testarosso SBS 250 L, Testarosso SBS 300 L, Technoply SBS BFG 140 S, Technoply SBS BFG 220 S, Technoply SBS BFG 300 S, Technoply SBS BP 250 S, Technoply SBS BP 300 S, Technoply SBS BP 400 S, Testarosso SBS 250 S, or Testarosso SBS 300 S, mechanically fastened or torched.

Membrane: — Technoply SBS FR SV 300 Aluminum Flake, Technoply SBS FR CFG 300 Aluminum Flake, Technoply SBS FR SV 350 Aluminum Flake, Technoply SBS FR CFG 350 Aluminum Flake, Technoply SBS FR SV 400 Aluminum Flake, Technoply SBS FR CFG 400 Aluminum Flake, Technoply SBS FR SP 300 Aluminum Flake, Technoply SBS FR SP 300 Aluminum Flake, Technoply SBS FR SP 350 Aluminum Flake, Technoply SBS FR SP 350 Aluminum Flake, Technoply SBS FR SP 400 Aluminum Flake, Technoply SBS FR SP 400 Aluminum Flake, torched.

7. **Deck:** NC

Incline: 1

Membrane: — Technoply SBS FR SV 300 Aluminum Flake, Technoply SBS FR CFG 300 Aluminum Flake, Technoply SBS FR SV 350 Aluminum Flake, Technoply SBS FR CFG 350 Aluminum Flake, Technoply SBS FR SV 400 Aluminum Flake, Technoply SBS FR CFG 400 Aluminum Flake, Technoply SBS FR SP 300 Aluminum Flake, Technoply SBS FR SP 300 Aluminum Flake, Technoply SBS FR SP 350 Aluminum Flake, Technoply SBS FR SP 350 Aluminum Flake, Technoply SBS FR SP 400 Aluminum Flake, Technoply SBS FR SP 400 Aluminum Flake, torched.

8. **Deck:** C-15/32

Incline: 1

Insulation (optional): — Polyisocyanurate , perlite, glass fiber, wood fiber, mineral fibreboard, any combination, any thickness, loose laid or mechanically fastened.

Barrier Board: — One or more layers Georgia-Pacific Gypsum LLC "DensDeck® Roofboard" or "DensDeck® Prime Roofboard" or "DensDeck® DuraGuard™ Roofboard", minimum 1/4-in. thick, or United States Gypsum Co. "SECUROCK® Roof Board" (Type FRX-G) or "SECUROCK® Glass-Mat Roof Board" (Type SGMRX), minimum 1/4-in. thick.

Base Sheet: — One or more plies Technoply SBS SV 140 L, Technoply SBS SV 220 L, Technoply SBS SV 300 L, Technoply SBS SP 250 L, Technoply SBS SP 300 L, Technoply SBS SP 400 L, Testarosso SBS 250 L, Testarosso SBS 300 L, Technoply SBS BFG 140 S, Technoply SBS BFG 220 S, Technoply SBS BFG 300 S, Technoply SBS BP 250 S, Technoply SBS BP 300 S, Technoply SBS BP 400 S, Testarosso SBS 250 S, or Testarosso SBS 300 S, mechanically fastened or torched.

Membrane: — Technoply SBS FR SV 300 Aluminum Flake, Technoply SBS FR CFG 300 Aluminum Flake, Technoply SBS FR SV 350 Aluminum Flake, Technoply SBS FR CFG 350 Aluminum Flake, Technoply SBS FR SV 400 Aluminum Flake, Technoply SBS FR CFG 400 Aluminum Flake, Technoply SBS FR SP 300 Aluminum Flake, Technoply SBS FR SP 300 Aluminum Flake, Technoply SBS FR SP 350 Aluminum Flake, Technoply SBS FR SP 350 Aluminum Flake, Technoply SBS FR SP 400 Aluminum Flake, Technoply SBS FR SP 400 Aluminum Flake, torched.

Class C

1. **Deck:** NC

Incline: 1/4

Base Sheet: — One or more plies Technoply SBS SV 140 L, Technoply SBS SV 220 L, Technoply SBS SV 300 L, Technoply SBS SP 250 L, Technoply SBS SP 300 L, Technoply SBS SP 400 L, Testarosso SBS 250 L, Testarosso SBS 300 L, Technoply SBS BFG 140 S, Technoply SBS BFG 220 S, Technoply SBS BFG 300 S, Technoply SBS BP 250 S, Technoply SBS BP 300 S, Technoply SBS BP 400 S, Testarosso SBS 250 S, or Testarosso SBS 300 S, mechanically fastened or torched.

Membrane: — Technoply SBS SV 300 G, Technoply SBS CFG 300 G, Technoply SBS SV 350 G, Technoply SBS CFG 350 G, Technoply SBS SV 400 G, Technoply SBS CFG 400 G, Technoply SBS SP 300 G, Technoply SBS SP 300 G, Technoply SBS SP 350 G, Technoply SBS SP 350 G, Technoply SBS SP 400 G, Technoply SBS SP 400 G, torched.

2. **Deck:** C-15/32

Incline: 1/4

Insulation (optional): — Polyisocyanurate , perlite, glass fiber, wood fiber, mineral fibreboard, any combination, any thickness, loose laid or mechanically fastened.

Barrier Board: — One or more layers Georgia-Pacific Gypsum LLC "DensDeck® Roofboard" or "DensDeck® Prime Roofboard" or "DensDeck® DuraGuard™ Roofboard", minimum 1/4-in. thick, or United States Gypsum Co. "SECUROCK® Roof Board" (Type FRX-G) or "SECUROCK® Glass-Mat Roof Board" (Type SGMRX), minimum 1/4-in. thick.

Base Sheet: — One or more plies Technoply SBS SV 140 L, Technoply SBS SV 220 L, Technoply SBS SV 300 L, Technoply SBS SP 250 L, Technoply SBS SP 300 L, Technoply SBS SP 400 L, Testarosso SBS 250 L, Testarosso SBS 300 L, Technoply SBS BFG 140 S, Technoply SBS BFG 220 S, Technoply SBS BFG 300 S, Technoply SBS BP 250 S, Technoply SBS BP 300 S, Technoply SBS BP 400 S, Testarosso SBS 250 S, or Testarosso SBS 300 S, mechanically fastened or torched.

Membrane: — Technoply SBS SV 300 G, Technoply SBS CFG 300 G, Technoply SBS SV 350 G, Technoply SBS CFG 350 G, Technoply SBS SV 400 G, Technoply SBS CFG 400 G, Technoply SBS SP 300 G, Technoply SBS SP 300 G, Technoply SBS SP 350 G, Technoply SBS SP 350 G, Technoply SBS SP 400 G, Technoply SBS SP 400 G, torched.

Last Updated on 2017-08-09

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".